## **FRIGIDAIRE** PROFESSIONAL.

## 1.8 Cu. Ft. 2-In-1 Over-The-Range Convection Microwave

Over-The-Range Microwave

Available Products: FPBM3077RF

Available Colors: Stainless Steel

Version: 08/22

## **Product Specifications**

Cooking Controls		Microwave Cooking	
Clock	Yes	Sensor Cooking	Yes
Number of Power Levels	9	Popcorn	Yes
Cooking Power	1050 Watts	Potato	Yes
		Melt / Soften	Yes
Ventilation System		Veggies	Yes
Exhaust Fan Speeds	4		
Charcoal Filter Included	Yes	Microwave Control Features	
Removable Grease Filter	Yes	+ 30 Seconds	No
Internal Specifications		Surface Light System	
Interior Light Wattage	40 Watts	Lighting Type	LED
Turntable Diameter	14 19/100"	Number of Lights	2
Turntable Material	Glass	¥	
		Electrical Specifications	
Dimensions and Volume		Voltage Rating	120 V
Height	17.563"		
Width	29 29/32"	General Specifications	
Depth	16.063"	Prop 65 Label	Yes
Microwave Interior Height	9 15/16"	Warranty - Labor	1 Year
Microwave Interior Width	21 1/4"	Warranty - Parts	1 Year
Microwave Interior Depth	14 23/32"		
Microwave Capacity	1.8 Cu. Ft.	Safety Certifications and Approvals	
		CSA Listed	No
Installation		UL Listed	Yes
Power Supply Connection Location	Right Top		
Certifications and Approvals			
ADA Compliant	No		

For planning purposes only. We reserve the right to change specifications or discontinue models without notice. Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca Electrolux Major Appliances, N.A.

USA • 10200 David Taylor Drive •Charlotte, NC 28262 • Charlotte, NC 28262 • 1-877-4electrolux (1-877-435-3287) • frigidaire.com CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca

1.8 Cu. Ft. 2-In-1 Over-The-Range Convection Microwave	Over-The-Range Microwave	
Available Products: FPBM3077RF	Available Colors: Stainless Steel	
Version: 08/22		

## **Installation Diagram**

Microwave MUST Bottom edge of cabinet MUST be be mounted to BOTH a top cabinet AND a wall\* 30" min. from cooking surface 12" 30" Cabinet MUST be min. Rear Wall capable of min. 13" supporting a total load of 135 lbs. 66" min. max. 30" min.from floor to top of 2"min. microwave Backsplash Power cord Blower plate allows for vertical location or horizontal ducting 17%16 \*Can NOT be installed rear in island or peninsula extrusion cabinet arrangements lower 297/8" extrusion 161/16" Allow at least 26" clearance for door depth when open

Refer to Product Installation Guide for detailed installation instructions on the web at frigidaire.com / frigidaire.ca Electrolux Major Appliances, N.A. USA • 10200 David Taylor Drive •Charlotte, NC 28262 • Charlotte, NC 28262 • 1-877-4electrolux (1-877-435-3287) • frigidaire.com

For planning purposes only. We reserve the right to change specifications or discontinue models without notice.

Locate 120V/60Hz grounded outlet inside upper cabinet

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • frigidaire.ca